

Lightning and Overvoltage Protection
ProBloc B(R) 100 (4+0)
 Class I • Class II • Type 1 • Type 2

25 kA Series



Location of Use: Main Distribution Boards
 Network Systems: TN-S
 Mode of Protection: L-PE, N-PE
 IEC/EN Category: Class I+II / Type 1+2
 Housing: Compact Design
 Compliance: IEC 61643-11:2011
 EN 61643-11:2012

Technical Data



ProBloc B(R) 100/xxx (4+0)		150	275*	320*
IEC Electrical				
Nominal AC Voltage (50/60 Hz)	U_o	120V	230V	230V
Maximum Continuous Operating Voltage (AC)	U_c	150V	275V	320V
Nominal Discharge Current (8/20 μ s)	I_n		25 kA	
Maximum Discharge Current (8/20 μ s)	I_{max}		100 kA	
Impulse Discharge Current (10/350 μ s)	I_{imp}		25 kA	
Total Discharge Current (10/350 μ s)	I_{total}		100 kA	
Specific Energy	W/R		156 kJ/ Ω	
Charge	Q		12.5 As	
Voltage Protection Level	U_p	< 1.0 kV	< 1.5 kV	< 1.5 kV
Response Time	t_A		< 25 ns	
Overcurrent Protection (max)			250 A gG	
Short-Circuit Current Rating (AC)	I_{SCCR}		50 kA	
TOV Withstand 5s	U_T	174V	334V	334V
TOV Safe Fail 120min	U_T	229V	438V	438V
Number of Ports			1	
Mechanical & Environmental				
Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]		
Permissible Humidity	RH	5%...95%		
Terminal Screw Torque	M_{max}	26.5 lbf-in [3.0 Nm]		
Conductor Cross Section (max)		2 AWG (Solid, Stranded) / 4 AWG (Flexible) 35mm ² (Solid, Stranded) / 25mm ² (Flexible)		
Mounting		35 mm DIN Rail, EN 60715		
Degree of Protection		IP 20 (built-in)		
Housing Material		Thermoplastic: Extinguishing Degree UL 94 V-0		
Thermal Protection		Yes		
Fault Indication		Red Flag		
Remote Contacts (RC)		Optional		
RC Switching Capacity		AC: 250V/0.5A; 125V/3A		
RC Terminal Cross Section (max)		1.5mm ² (Solid) / 16 AWG (Solid)		
RC Terminal Screw Torque	M_{max}	2.2 lbf-in [0.25 Nm]		
Order Information				
Order Code		150	275*	320*
ProBloc B 100/xxx (4+0)		56.0592	56.0594	56.0596
ProBloc BR 100/xxx (4+0) (with remote contacts)		56.0593	56.0595	56.0597

*OVE Certified


Internal Configuration

Legend

- L Line Conductor Terminal
- N Neutral Conductor Terminal
- ⏚ PE Conductor Terminal
- RC Remote Contacts Terminal (Optional)
- TD Thermal Disconnect



Complete Unit



Single Unit Dimensions & Packaging

		150	275*	320*
ProBloc B 100/xxx (4+0)				
Weight	pounds	2.028	2.469	2.469
	grams	920	1120	1120
DIN 43880 Dimension		8 TE / 5.66" [144]		
Packaging Dimensions (H x W x L)		3.1 x 4.4 x 11.7" [79 x 112 x 298 mm]		
Standard Order Quantity		2 Units		
ProBloc BR 100/xxx (4+0)				
Weight	pounds	2.182	2.623	2.623
	grams	990	1190	1190
DIN 43880 Dimension		8 TE / 5.66" [144]		
Packaging Dimensions (H x W x L)		3.1 x 4.4 x 11.7" [79 x 112 x 298 mm]		
Standard Order Quantity		2 Units		



inches
[mm]